

# COMPARE

## BLOW<sup>R</sup> BUDDI



## BLOW<sup>R</sup> MINI



## BLOW<sup>R</sup> MINI +



## BLOW<sup>R</sup> PRO



1000 watts' max



2 stage wind control



Heated air with single filter



Fixed. 25°C higher than the surrounding environment



Noise reduction system



CFM/FPM 19,680 ft/min



DB RATING Low 73 High 78



Hose length 1,5 m (optional)



Power cord 2,4 m



N/A



N/A



25 x 22 x 13 cm

1600 watts' max motor plus 1000 watt heating element. Total 2600 watts' max

2 stage adjustable wind control

Heated air with single filter

Working temp from 15°C - 45°C

Noise reduction system

CFM/FPM 32,000 ft/min

Low 73 High 79

Hose length 5 m

Power cord 5 m

Wheel base dolly (optional)

Vacuum optional

24 x 24 x 38 cm

2800 watts' max twin motor

3 stage adjustable wind control

Heated air with single filter

Working temp from 15°C - 40°C

Noise reduction system

CFM/FPM of 58,600 ft/min

Low at 75 High at 81

Hose length 5 m

Power cord 5 m

Wheel base front pivot dolly (optional)

Vacuum optional

53 x 24,5 x 24 cm

3200 watts' max twin motor

4 stage wind control

Heated air with twin filters

Fixed. 20°C higher than the surrounding environment

Noise reduction system

CFM/FPM 59,200 ft/min

Low 75 High 81

Hose length 5 m

Power cord 5 m

Attached wheel base with front pivot wheels

N/A

45 x 40 x 20 cm